ViewSonic VG2437SMC 24 inch (23.6 inch VIS) Full HD MVA LED Monitor/2MP Webcam/Dual Speakers/DisplayPort/DVI/VGA/2-port USB

Display Size (in.):	24
Viewable Area (in.):	23.6
Panel Type:	MVA
Resolution:	1920 x 1080
Static Contrast Ratio:	3,000:1
Dynamic Contrast Ratio:	20,000,000:1
Light Source:	LED
	250 cd/m2
Colors:	16.7M
Response Time (Typical GTG):	7ms
	178º horizontal, 178º vertical
	40,000
	3H Anti-glare, hard-coating
PC Resolution (max):	1920 x 1080
Mac® Resolution (max):	1920 x 1080
Internal Speakers:	2-watt (x2)
Eco Mode (Conserve):	15.5W
Eco Mode (optimized):	19W
	25W
	39W
	AC 100-240V (universal), 50-60Hz
Microphone:	2
Kensington Lock Slot:	1
	2MP
	1.2 Down Up Power
Physical Controls: On Screen Display:	1, 2, Down, Up, Power Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality)
Physical Controls: On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See
Physical Controls: On Screen Display: Temperature:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality)
Physical Controls: On Screen Display: Temperature: Humidity (non-condensing):	Auto Image Adjust, Contrast/Brightness, Input Select,Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C)
Physical Controls: On Screen Display: Temperature: Humidity (non-condensing): VESA Compatible:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90%
Physical Controls: On Screen Display: Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal:	Auto Image Adjust, Contrast/Brightness, Input Select,Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm
Physical Controls: On Screen Display: Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24~82kHz
Physical Controls: On Screen Display: Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync:	Auto Image Adjust, Contrast/Brightness, Input Select,Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24-82kHz 50~75Hz
Physical Controls: On Screen Display: Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24~82kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green
Physical Controls: On Screen Display: Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel:	Auto Image Adjust, Contrast/Brightness, Input Select,Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24-82kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 135
Physical Controls: On Screen Display: Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24~82kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 135 360°
Physical Controls: On Screen Display: Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back):	Auto Image Adjust, Contrast/Brightness, Input Select,Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24-82kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 135 360° 90° / 0°
Physical Controls: On Screen Display: Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (lbs):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24~82kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 135 360° 90° / 0° 3° / 25°
Physical Controls: On Screen Display: Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (lbs): Net Without Stand (lbs):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24~82kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 135 360° 90° / 0° 3° / 25° 11.5
Physical Controls: On Screen Display: Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (lbs): Net Without Stand (lbs): Gross (lbs):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24~82kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 135 360° 90° / 0° 3° / 25° 11.5 8.3
Physical Controls: On Screen Display: Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (lbs): Net Without Stand (lbs): Gross (lbs): Net (kg):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24~82kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 135 360° 90° / 0° 3° / 25° 11.5 8.3 15.5
Physical Controls: On Screen Display: Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (lbs): Net Without Stand (lbs): Gross (lbs): Net Without Stand (kg):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24~82kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 135 360° 90° / 0° 3° / 25° 11.5 8.3 15.5 5.2
Physical Controls: On Screen Display: Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (lbs): Net Without Stand (lbs): Gross (lbs): Net Without Stand (kg): Gross (kg):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24~82kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 135 360° 90° / 0° 3° / 25° 11.5 8.3 15.5 5.2 3.7
Physical Controls: On Screen Display: Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (lbs): Net Without Stand (lbs): Gross (lbs): Net Without Stand (kg): Gross (kg): Packaging (in.):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24~82kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 135 360° 90° / 0° 3° / 25° 11.5 8.3 15.5 5.2 3.7 7.1
Physical Controls: On Screen Display: Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (lbs): Net Without Stand (lbs): Gross (lbs): Net (kg): Net Without Stand (kg): Gross (kg): Packaging (in.): Physical (in.):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24~82kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 135 360° 90° / 0° 3° / 25° 11.5 8.3 15.5 5.2 3.7 7.1 24.8 x 20.8 x 5.6
Physical Controls: On Screen Display: Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (lbs): Net Without Stand (lbs): Gross (lbs): Net (kg): Net Without Stand (kg): Gross (kg): Packaging (in.): Physical (in.): Physical Without Stand (in.):	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 24-82kHz 50-75Hz Separate Sync, Composite Sync, Sync on Green 135 360° 90° / 0° 3°/ 25° 11.5 8.3 15.5 5.2 3.7 7.1 24.8 x 20.8 x 5.6 21.9 x 17.8 x 9.4

Physical (mm):	556.8 x 450.9 x 239.6
Physical Without Stand (mm):	556.8 x 340.3 x 60.5
MX-CoC, CE, EMC, WEEE, RoHS, CB, TCO7.0, GS, Erp. EAC, UkrSEPRO	
USB 2.0 Type A(2), USB 2.0 Type B(1), 3.5mm Mic In(1), 3.5mm Mic Out(1), 3.5mm Audio In(1), 3.5mm Audio Out(1), VGA(1), DVI-D(1), Display Port(1)	
PACKAGE CONTENTS:	VG2437Smc monitor, Power cable, VGA cable, DVI cable, USB cable, Audio cable, Mic cable, Quick Start Guide
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	Three-year limited warranty on parts, labor and backlight
UPC:	766907782622