ViewSonic VG2438SM 24 inch High-Performance SuperClear IPS Display with DisplayPort/DVI/VGA and 4-Port USB Hub

Display Size (in.):	24
Panel Type:	IPS
Resolution:	1920 x 1200
Static Contrast Ratio:	1,000:1
Dynamic Contrast Ratio:	50,000,000:1
Light Source:	LED
Brightness:	250 cd/m2
Colors:	16.7M
Response Time (Typical GTG):	5ms
Viewing Angles:	178º horizontal, 178º vertical
Backlight Life (Hours):	40,000
Panel Surface:	3H Anti-glare, hard-coating
PC Resolution (max):	1920 x 1200
Mac® Resolution (max):	1920 x 1200
Internal Speakers:	2-watt (x2)
Eco Mode (Conserve):	17.5W
Eco Mode (optimized):	22W
Consumption (typical):	30W
Consumption (max):	32W
Voltage:	AC 100-240V (universal), 50-60Hz
vollage.	1
Kensington Lock Slot:	1
Physical Controls:	1, 2, Down, Up, Power
	Autologica Adicat Control (Drielstone Legant Cologt Audio Adicat Colog
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select,Audio Adjust, Color Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality)
On Screen Display: Temperature:	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See
	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality)
Temperature: Humidity (non-condensing):	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C)
Temperature: Humidity (non-condensing): VESA Compatible:	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm
Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal:	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 30~80kHz
Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical:	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 30~80kHz 50~75Hz
Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync:	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 30~80kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green
Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm):	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 30~80kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green
Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel:	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 30~80kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 100 360°
Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left):	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 30~80kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 100 360° 90° / 0°
Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back):	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 30~80kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 100 360° 90° / 0° 5° / 37°
Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (lbs):	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 30~80kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 100 360° 90° / 0° 5° / 37° 12.7
Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (lbs): Net Without Stand (lbs):	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 30~80kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 100 360° 90° / 0° 5° / 37° 12.7
Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (lbs): Net Without Stand (lbs): Gross (lbs):	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 30~80kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 100 360° 90° / 0° 5° / 37° 12.7 9.2 16.2
Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (lbs): Net Without Stand (lbs): Gross (lbs): Net (kg):	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 30~80kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 100 360° 90° / 0° 5° / 37° 12.7 9.2 16.2 5.7
Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (lbs): Net Without Stand (lbs): Gross (lbs): Net (kg): Net Without Stand (kg):	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 30~80kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 100 360° 90° / 0° 5° / 37° 12.7 9.2 16.2 5.7 4.2
Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (lbs): Net Without Stand (lbs): Gross (lbs): Net (kg): Net Without Stand (kg): Gross (kg):	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 30~80kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 100 360° 90° / 0° 5° / 37° 12.7 9.2 16.2 5.7 4.2
Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (lbs): Net Without Stand (lbs): Gross (lbs): Net Without Stand (kg): Gross (kg): Packaging (in.):	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 30~80kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 100 360° 90° / 0° 5° / 37° 12.7 9.2 16.2 5.7 4.2
Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (Ibs): Net Without Stand (Ibs): Gross (Ibs): Net Without Stand (kg): Gross (kg): Packaging (in.): Physical (in.):	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 30~80kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 100 360° 90° / 0° 5° / 37° 12.7 9.2 16.2 5.7 4.2
Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (lbs): Net Without Stand (lbs): Gross (lbs): Net Without Stand (kg): Gross (kg): Packaging (in.):	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 30~80kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 100 360° 90° / 0° 5° / 37° 12.7 9.2 16.2 5.7 4.2 7.4
Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (libs): Net Without Stand (lbs): Gross (lbs): Net Without Stand (kg): Gross (kg): Packaging (in.): Physical (in.):	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 30~80kHz 50~75Hz Separate Sync, Composite Sync, Sync on Green 100 360° 90° / 0° 5° / 37° 12.7 9.2 16.2 5.7 4.2 7.4 24.0 x 16.9 x 6.5 21.9 x 15.5 x 8.0
Temperature: Humidity (non-condensing): VESA Compatible: Frequency Horizontal: Frequency Vertical: Analog Sync: Height Adjust (mm): Swivel: Pivot (Right/Left): Tilt (Forward/Back): Net (lbs): Net Without Stand (lbs): Gross (lbs): Net (kg): Net Without Stand (kg): Gross (kg): Packaging (in.): Physical Without Stand (in.):	Adjust, Information, Manual ImageAdjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) 32-104° F (0 - 40° C) 20-90% 100 x 100 mm 30-80kHz 50-75Hz Separate Sync, Composite Sync, Sync on Green 100 360° 90° / 0° 5° / 37° 12.7 9.2 16.2 5.7 4.2 7.4 24.0 x 16.9 x 6.5 21.9 x 15.5 x 8.0 21.9 x 14.3 x 2.0

Physical Without Stand (mm):	556.8 x 363 x 51.5
USB 3.0 Type A(4), 3.5mm Audio In(1), VGA(1), DVI-D(1), Di	splay Port(1)
Regulations:	cULus, FCC-B, Energy Star 6.0, EPEA GOLD, AR-S, UL-MX-CoC, Mexico Energy, Custom Union, UkrSEPRO + DoC, GS, Ergo, CE, CB, ErP, REACH SVHC List & Doc, RoHS Green BOM List & RoHS DoC, WEEE, TCO6.0, Windows 8
PACKAGE CONTENTS:	VG2438Sm display, Power cable, VGA cable, DVI Cable, DisplayPort cable, Audio cable, Quick Start Guide, ViewSonic Wizard CD (User Guide)
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	Three-year limited warranty on parts, labor and backlight
UPC:	766907782516