ViewSonic VG2439SMH 24 inch (23.6 inch VIS) Full HD LED SuperClear MVA Multimedia Monitor/HDMI/DisplayPort/VGA/2 USB Ports

Display Size (in.): 24 Viewable Area (in.): 23.6 Panel Type: MVA Resolution: 1920 x 1080 Static Contrast Ratio: 3,000:1 Dynamic Contrast Ratio: 20,000,000:1 Light Source: LED Brightness: 250 cd/m2 Colors: 16.7M Response Time (Typical GTG): 7ms Viewing Angles: 178° horizontal, 178° vertical Backlight Life (Hours): 40,000 Panel Surface: 3H Anti-glare, hard-coating PC Resolution (max): 1920 x 1080 Mac® Resolution (max): 1920 x 1080 Internal Speakers: 2-watt (x2) Eco Mode (Conserve): 16W Eco Mode (optimized): 19W Consumption (typical): 23W Consumption (max): AC 100-240V (universal), 50-60Hz Voltage:	
Panel Type: MVA Resolution: 1920 x 1080 Static Contrast Ratio: 3,000:1 Dynamic Contrast Ratio: 20,000,000:1 Light Source: LED Brightness: 250 cd/m2 Colors: 16.7M Response Time (Typical GTG): 7ms Viewing Angles: 178º horizontal, 178º vertical Backlight Life (Hours): 40,000 Panel Surface: 3H Anti-glare, hard-coating PC Resolution (max): 1920 x 1080 Mac® Resolution (max): 1920 x 1080 Internal Speakers: 2-watt (x2) Eco Mode (Conserve): 16W Eco Mode (optimized): 19W Consumption (typical): 23W Consumption (max): 36W	
Resolution: 1920 x 1080 Static Contrast Ratio: 3,000:1 Dynamic Contrast Ratio: 20,000,000:1 Light Source: LED Brightness: 250 cd/m2 Colors: 16.7M Response Time (Typical GTG): 7ms Viewing Angles: 178º horizontal, 178º vertical Backlight Life (Hours): 40,000 Panel Surface: 3H Anti-glare, hard-coating PC Resolution (max): 1920 x 1080 Mac® Resolution (max): 1920 x 1080 Internal Speakers: 2-watt (x2) Eco Mode (Conserve): 16W Eco Mode (optimized): 19W Consumption (typical): 23W Consumption (max): 36W AC 100-240V (universal), 50-60Hz	
Static Contrast Ratio: 3,000:1 Dynamic Contrast Ratio: 20,000,000:1 Light Source: LED Brightness: 250 cd/m2 Colors: 16.7M Response Time (Typical GTG): 7ms Viewing Angles: 178° horizontal, 178° vertical Backlight Life (Hours): 40,000 Panel Surface: 3H Anti-glare, hard-coating PC Resolution (max): 1920 x 1080 Mac® Resolution (max): 1920 x 1080 Internal Speakers: 2-watt (x2) Eco Mode (Conserve): 16W Eco Mode (optimized): 19W Consumption (typical): 23W Consumption (max): 36W	
Dynamic Contrast Ratio:	
Light Source: Brightness: Colors: 16.7M Response Time (Typical GTG): Viewing Angles: Backlight Life (Hours): Panel Surface: PC Resolution (max): Mac® Resolution (max): Internal Speakers: Eco Mode (Conserve): Eco Mode (optimized): Consumption (typical): Consumption (max): Bightness: 250 cd/m2 240,000 7ms 40,000 40,000 1920 x 1080 1920 x 1080 1920 x 1080 1920 x 1080 1940 x 1080 1950 x 1080 1960 x 1080 1970 x 1080 1980 x 1080 1980 x 1080 x 1080 1980	
Brightness: 250 cd/m2 Colors: 16.7M Response Time (Typical GTG): 7ms Viewing Angles: 178° horizontal, 178° vertical Backlight Life (Hours): 40,000 Panel Surface: 3H Anti-glare, hard-coating PC Resolution (max): 1920 x 1080 Mac® Resolution (max): 1920 x 1080 Internal Speakers: 2-watt (x2) Eco Mode (Conserve): 16W Eco Mode (optimized): 19W Consumption (typical): 23W Consumption (max): 36W AC 100-240V (universal), 50-60Hz	
Colors: 16.7M Response Time (Typical GTG): 7ms Viewing Angles: 178° horizontal, 178° vertical Backlight Life (Hours): 40,000 Panel Surface: 3H Anti-glare, hard-coating PC Resolution (max): 1920 x 1080 Mac® Resolution (max): 1920 x 1080 Internal Speakers: 2-watt (x2) Eco Mode (Conserve): 16W Eco Mode (optimized): 19W Consumption (typical): 23W Consumption (max): 36W AC 100-240V (universal), 50-60Hz	
Response Time (Typical GTG): Viewing Angles: Backlight Life (Hours): Panel Surface: PC Resolution (max): Mac® Resolution (max): Internal Speakers: Eco Mode (Conserve): Eco Mode (optimized): Consumption (typical): Consumption (max): 7ms 7ms 7ms 178° horizontal, 178° vertical 40,000 1920 x 1080 1920 x 1080 1920 x 1080 1920 x 1080 1940 1950 x 1080 1960 1970 x 1080 1970 x	
Viewing Angles: Backlight Life (Hours): Panel Surface: PC Resolution (max): Mac® Resolution (max): Internal Speakers: Eco Mode (Conserve): Eco Mode (optimized): Consumption (typical): Consumption (max): 178° horizontal, 178° vertical 40,000 3H Anti-glare, hard-coating 1920 x 1080 1920 x 1080 1920 x 1080 1940 x 1080 1950 x 1080 1970 x 10	
Backlight Life (Hours): Panel Surface: 3H Anti-glare, hard-coating PC Resolution (max): 1920 x 1080 Mac® Resolution (max): 1920 x 1080 Internal Speakers: 2-watt (x2) Eco Mode (Conserve): 16W Eco Mode (optimized): 19W Consumption (typical): 23W Consumption (max): 36W AC 100-240V (universal), 50-60Hz	
Panel Surface: Panel Surface: 3H Anti-glare, hard-coating PC Resolution (max): 1920 x 1080 Mac® Resolution (max): 1920 x 1080 Internal Speakers: 2-watt (x2) Eco Mode (Conserve): 16W Eco Mode (optimized): Consumption (typical): 23W Consumption (max): 36W AC 100-240V (universal), 50-60Hz	
PC Resolution (max): 1920 x 1080 Mac® Resolution (max): 1920 x 1080 Internal Speakers: 2-watt (x2) Eco Mode (Conserve): 16W Eco Mode (optimized): 19W Consumption (typical): 23W Consumption (max): 36W AC 100-240V (universal), 50-60Hz	
Mac® Resolution (max): 1920 x 1080 Internal Speakers: 2-watt (x2) Eco Mode (Conserve): 16W Eco Mode (optimized): 19W Consumption (typical): 23W Consumption (max): 36W AC 100-240V (universal), 50-60Hz	
Internal Speakers: Eco Mode (Conserve): Eco Mode (optimized): Consumption (typical): Consumption (max): 36W AC 100-240V (universal), 50-60Hz	
Eco Mode (Conserve): Eco Mode (optimized): Consumption (typical): Consumption (max): 36W AC 100-240V (universal), 50-60Hz	
Eco Mode (optimized): Consumption (typical): Consumption (max): 36W AC 100-240V (universal), 50-60Hz	
Consumption (typical): Consumption (max): 36W AC 100-240V (universal), 50-60Hz	
Consumption (max): 36W AC 100-240V (universal), 50-60Hz	
AC 100-240V (universal), 50-60Hz	
Voltage:	
I	
Kensington Lock Slot:	
Physical Controls: 1, 2, Down, Up, Power	
Auto Image Adjust, Contrast/Brightnes On Screen Display: Adjust, Information, Manual ImageAdj	
user guide for complete OSD functions	
Temperature: 32-104° F (0 - 40° C)	•
Humidity (non-condensing): 20-90%	
VESA Compatible: 100 x 100 mm	
Frequency Horizontal: 24~82kHz	
Frequency Vertical: 50~75Hz	
Analog Sync: Separate Sync, Composite Sync, Sync	oc on Green
Height Adjust (mm): 135	0 011 010011
Swivel: 360°	
Pivot (Right/Left): 90° / 0°	
Tilt (Forward/Back): 5º / 20°	
Net Without Stand (lbs): 8.2	
Gross (lbs): 15.3	
Net (kg): 5.2	
Net Without Stand (kg): 3.7	
Gross (kg): 6.9	
Packaging (in.): 25 x 20 x 7.5	
Physical (in.): 22.1 x 17.1 x 9.4	
Physical Without Stand (in.): 22.1 x 13.1 x 2.3	
Packaging (mm): 634 x 508 x 190	

Physical (mm):	560.3 x 435.2 x 239.6	
Physical Without Stand (mm):	560.3 x 332.7 x 58.2	
USB 2.0 Type A(2), USB 2.0 Type B(1), 3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Display Port(1)		
Regulations:	WEEE, RoHS, CE, CB, WHQL, UL/cUL, FCC-B,ENERGY STAR 7.0, REACH SVHC list & DoC, EEL, TCO6.0, EPEAT Silver, Mexico Energy, UkrSEPRO+Doc, ErP,	
PACKAGE CONTENTS:	VG2439Smh monitor, Power cable, VGA cable, DisplayPort cable, Audio cable, USB cable,Quick Start Guide, ViewSonic Wizard CD (User Guide)	
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.	
Warranty:	Three-year limited warranty on parts, labor and backlight	
UPC:	766907801910	