

Gefen EXT-UHDV-WP-HBTL5-TX 4K UHD Multi-Format 2x1 HDMI/HDBaseT Wall-Plate Extender (Transmitter) with Scaler/Auto-Switching/POH

- Recommended Receiver: EXT-UHDA-HBTL-RX
- Maximum TMDS Clock: 300 MHz
- Total Signal Bandwidth/Data Rate: 10.2 Gbps
- Video Input Connector:
 - (1) HDMI Type A 19-pin, female, locking
 - (1) VGA HD-15, female
- L/R Analog Audio Input port: (1) 3.5mm mini-stereo jack
- Link Connector: (1) RJ-45, shielded
- RS-232 port: (1) 4-pin Phoenix
- DC In port: (1) 2-pin Phoenix
- Firmware Update port: (1) USB-Mini-B, female
- Power Indicator LED: (1) Blue
- Link Indicator LED: (1) Green
- HDCP Indicator LED: (1) Green
- HDMI Input Indicator LED: (1) Green
- VGA Input Indicator LED: (1) Green
- Auto-Manual Switch: (1) tact-type
- Power Requirement: Powered through POH from a compatible Receiver (recommended), or via the Phoenix connector on back panel, using a hard-wired 12V 1~2A DC power supply
- Recommended Power Supply (sold separately): EXT-PS121.5AIP-3P-6 (DC plug needs to be removed)
- Power Consumption: 6W maximum
- Operating Temperature: +32 to +122 °F (0 to +50 °C)
- Operating Humidity: 5% to 90% RH, non-condensing
- Storage Temperature: -4 to +185 °F (-20 to +85 °C)
- Storage Humidity: 0% to 95% RH, non-condensing
- MTBF: 50000 hours
- Overall Dimensions (W x H x D, not including the connectors): 3.5" x 4.2" x 1.74" (89mm x 104.5mm x 44mm)
- Mounting Cavity Dimensions (W x H x D, behind the mounting plate): 3.6" x 2.8" x 2" (92mm x 72mm x 50mm)
- Net Weight: 0.6 lbs (0.27 kg)
- Shipping Weight: 0.9 lbs (0.4 kg)

* Features and specifications are subject to change without notice.