

**Electro-Voice ELX20012PUS 12 inch 2-Way powered speaker/51 Hz - 20 kHz/US cord**

<b>Weight Net</b>	15.6kg (34.39 lbs)
<b>Depth</b>	344mm (13.54")
<b>Width</b>	363mm (14.29")
<b>Height</b>	629mm (24.76")
<b>Available Color</b>	Black
<b>Connector Type</b>	(1) Stereo RCA Input, (2) XLR/TRS combo jack, and (1) XLR
<b>Coverage (Nominal -6 dB) H</b>	90°
<b>Coverage (Nominal -6 dB) V</b>	60°
<b>Crossover Frequency</b>	1700Hz
<b>Enclosure Material</b>	Polypropylene Composite
<b>Family</b>	ELX200
<b>Frequency Range (-10 dB)</b>	51 Hz - 20 kHz
<b>Frequency Response (-3 dB)</b>	57 Hz - 16 kHz
<b>Grille</b>	18 AWG steel with powdercoat
<b>HF Transducer</b>	DH-1C 1-inch titanium compression driver
<b>LF Transducer</b>	EVS-12M 300 mm (12 in)
<b>Max. SPL/1m (calc)</b>	130dB
<b>Power Consumption</b>	100 - 240 V~, 50 - 60 Hz, 1.8A
<b>Power Rating</b>	1200W
<b>Powered or Passive</b>	Powered
<b>Shipping Weight</b>	17.7kg (39.02 lbs)
<b>Speaker Type</b>	Full-Range
<b>Suspension</b>	(3) M10 suspension points
<b>Woofer Size</b>	12inch