

Electro-Voice EKX12PUS 1500 Watt Powered 12 inch Two Way Loudspeaker/50Hz-20kHz

Frequency Range (-10 dB)	50 Hz - 20 kHzkHz (Full space measurement using the music DSP preset.)
Weight Net	18.8kg (41.45 lbs)
Depth	356mm (14.02")
Width	375mm (14.76")
Height	607mm (23.9")
Connector Type	(1) Stereo RCA input, (2) XLR/TRS combo jack, and (1) XLR link output
Coverage (Nominal -6 dB) H	90°
Coverage (Nominal -6 dB) V	60°
Crossover Frequency	1.7 kHz
Enclosure Material	15 mm, plywood with EVCoat
Family	EKX
Frequency Response (-3 dB)	60 Hz - 18 kHzkHz (Full space measurement using the music DSP preset.)
Grille	18 AWG steel with powdercoat
HF Transducer	DH-1M 1-inch titanium compression driver
LF Transducer	EVS-12M 300 mm (12 in)
Max. SPL/1m (calc)	132dB
Maximum SPL	132 dBdB (Maximum SPL is measured at 1 m using broadband pink noise at maximum output.)
Power Consumption	1.8 A (Current rating is 1/8 power)
Power Rating	1500W
Powered or Passive	Powered
Shipping Weight	22.9kg (50.49 lbs)
Speaker Type	Full-Range, two-way
Suspension	(8) M10 threaded mounting points
Woofers Size	12inch