

Electro-Voice ETX10PUS Performance High Power active 10 inch 2 way speaker/2000W/65 Hz-20 kHz

Weight Net	20.3kg (44.75 lbs)
Depth	365mm (14.37")
Width	330mm (12.99")
Height	526mm (20.71")
Connector Type	(2) XLR/TRS combo jack and (1) XLR link output
Coverage (Nominal -6 dB) H	90°
Coverage (Nominal -6 dB) V	60°
Crossover Frequency	1700Hz
Enclosure Material	18-mm, 13-ply birch plywood with EVCoat
Family	ETX
Frequency Range (-10 dB)	65 Hz - 20 kHz (Full space measurement using the music DSP preset and 150 Hz low pass.)
Frequency Response (-3 dB)	85 Hz - 20 kHz (Full space measurement using the music DSP preset and 150 Hz low pass.)
Grille	16AWG steel with powdercoat
HF Transducer	DH3-B 1.25-in titanium compression driver
LF Transducer	SMX2100 254 mm (10 in)
Max. SPL/1m (calc)	134dB
Maximum SPL	134 peakdB (Maximum SPL is measured at 1 m using broadband pink noise at maximum output.)
Power Consumption	100 - 240 V~, 50 - 60 Hz, 1.6 - 0.8 A (Current rating is 1/8 power.)
Power Rating	2000W
Powered or Passive	Powered
Shipping Weight	22.9kg (50.49 lbs)
Speaker Type	Full-Range, two-way
Suspension	(8) M10 suspension points
Woofers Size	15inch