

Electro-Voice ETX15PUS Performance High Power active 15 inch 2 way speaker/2000W/40Hz-20kHz

Weight Net	27.7kg (61.07 lbs)
Depth	447mm (17.6")
Width	431mm (16.97")
Height	691mm (27.2")
Connector Type	(2) XLR/TRS combo jack and (1) XLR link output
Coverage (Nominal -6 dB) H	90°
Coverage (Nominal -6 dB) V	60°
Crossover Frequency	1500Hz
Enclosure Material	18-mm, 13-ply birch plywood with EVCoat
Family	ETX
Frequency Range (-10 dB)	40 Hz - 20 kHz
Frequency Response (-3 dB)	48 Hz - 20 kHz
Grille	16AWG steel with powdercoat
HF Transducer	DH3-B 1.25-in titanium compression driver
LF Transducer	SMX2150 380 mm (15 in)
Max. SPL/1m (calc)	135dB
Maximum SPL	135 dB peakdB
Power Consumption	100 - 240 V~, 50 - 60 Hz, 1.6 - 0.8 A
Power Rating	2000W
Powered or Passive	Powered
Shipping Weight	31.5kg (69.45 lbs)
Speaker Type	Full-Range, two-way, powered speakers
Suspension	(8) M10 suspension points
Woofers Size	15inch