

Electro-Voice CP4000S120V CP Series 2RU Amplifier (2x 2100W/2 Ohms - 2x 1500W/4 Ohms - 2x 900W/8 Ohms)

Output Power	2100W @ 2Ω Stereo (per channel) 1500W @ 4Ω Stereo (per channel) 900W @ 8Ω Stereo (per channel) 4200W @ 4Ω Bridged-Mono 3000W @ 8Ω Bridged-Mono
Damping Factor	> 300
Input Sensitivity	+7 dBu (1.74 V RMS)
Input Impedance	20 k ohms
Gain	32dB
Frequency Response	15Hz - 40kHz, +/-1dB
Signal-to-Noise Ratio	108dB (A-Weighted)
Total Harmonic Distortion (THD)	<0.05%
Input Connections	2 x XLR Female (Balanced)
Output Connectors	2 x XLR Male 3 x Neutrik Speakon Connectors
Controls Front Panel	1 x Power Switch 2 x Input Level Controls
Controls (Rear)	1 x Grounded/Ungrounded Switch 1 x Bridged Mode Switch 1 x Dual/Parallel Routing Switch
Indicators	2 x Red Limiter LEDs 2 x Yellow 0dB LEDs 2 x Green Signal Present LEDs 1 x Red Protection Circuitry LED 1 x Green Power LED
Cooling	3-Stage Fan Cooled, Front-to-Rear Airflow
Power Consumption	1070W (1/8 Max Output Power @ 4 ohms)
Power Requirements	100 VAC, 120 VAC, 220 VAC, 240 VAC
Dimensions (WxHxD)	19 x 3.5 x 14.5" (483 x 88 x 369 mm)
Weight	19.2 lbs (8.7 kg)
Specialties	Comprehensive Protection Circuitry
Packaging Info	
Package Weight	24.55 lb
Box Dimensions (LxWxH)	22.3 x 20.6 x 8.2"