

Tannoy CVS 6 BK 6 inch Coaxial In-Ceiling Loudspeaker for Installation Applications/Black

Performance	
Frequency response (-3 dB) (1)	79 Hz - 21 kHz
Frequency range (-10 dB) (1)	60 Hz - 24 kHz
System sensitivity (1 W @ 1m) (2)	91 dB (1 W = 2.45 V for 6 Ohms)
Nominal Coverage Angle	90 degrees conical
Coverage Angle (1 kHz to 6 kHz)	93 degrees
Directivity Factor (Q)	7.7 averaged 1 kHz to 6 kHz
Directivity Index (DI)	8 averaged 1 kHz to 6 kHz
Rated Maximum SPL	109 dB (average)
	115 dB (peak)
Power Handling ³	
Average	60 W
Programme	120 W
Peak	240 W
Recommended Amplifier Power	120 W @ 6 Ohms
Nominal Impedance	6 Ohms
Transformer Taps (via front rotary switch)	
70 V	60 W / 30 W / 15 W / 7.5 W / OFF & low impedance operation
100 V	60 W / 30 W / 15 W / OFF & low impedance operation
Transducers	
Low Frequency	150 mm (6.00") mineral loaded polypropylene ICT™
High Frequency	19 mm (0.75")
Physical	
Enclosure	
Back can	Zinc plated steel
Baffle	Refl ex loaded UL 94V-0 rated ABS
Grille	Steel, with weather resistant coating
Safety Features	Safety ring located at rear of enclosure for load bearing safety bond
Net Weight (ea)	5.7 kg (12.6 lbs)
Shipped weight	5.7 kg (12.68 lbs)
Included Accessories	C Ring, tile bridge, paint mask, cutout template, grille
Optional Accessories	Plaster (mud) ring