

Tannoy OCV 8-WH 8 inch Coaxial Pendant Loudspeaker for Installation Applications (White)

Performance	
Frequency Response (-3 dB) (1)	75 Hz-20 kHz
Frequency Range (-10 dB) (1)	60 Hz-30 kHz
System Sensitivity (1 W @1 m) (2)	90 dB
Dispersion (-6 dB)	80 degrees conical
Transducers	Coaxial
Low Frequency	200 mm (8.00") mineral loaded cone material
High Frequency	25 mm (1.00")
Crossover	4.5 kHz - 3rd order LF, 2d order HF
Directivity (Q)	14.4 averaged 1 kHz to 6.3 kHz
Directivity (DI)	11.6 dB averaged 1 kHz to 6.3 kHz
Rated Maximum SPL (2)	108 dB (average) 114 dB (peak)
Power Handling	
Average	70 W
Programme	140 W
Peak	280 W
Recommended Amplifier Power	140 W @ 16 Ω
Nominal Impedance	16 Ω
Construction	
Enclosure	ABS / Steel
Grille	Steel, plated and powder coat painted
Connectors	Euroblock type removable locking connector with screw terminals with "loop through" facility
Transformer setting	Rotary switch
Safety Agency Ratings	UL-1480, UL-2043, CE
Bezel diameter	302 mm (11.9")
Overall Length	493 mm (19.4")
Net Weight	8.2 kg (18.1 lbs)
Shipped weight	10.4 kg (22.9 lbs)
Transformer Taps 70 V 100 V	60 W / 30 W / 15 W / 7.5 W & low Impedance operation 60 W / 30 W / 15 W & low Impedance operation