

Sierra Video 3216ASR-128-MA 32x16 Stereo Audio Master Router Redundant PS 5RU

Rack Unit Size / Frame	
64x64 Audio Frames	3RU
128x128 Audio Frame	5RU
Dimensions	
64x64 Audio Frames	19" w x 5.25" h x 19" d
128x128 Audio Frames	19" w x 8.75" h x 19" d
Power	
Power	90 VAC->240 VAC 50/60 HZ (<150 Watts) auto-detecting
Frequency Response	
Frequency Response	20HZ to 20KHz +/-0.1dB
Serial	
Serial	2 General Purpose 9 pin-D each switchable RS-232 or RS-422 9600, 38400, 115200 baud
Dynamic Range	
Dynamic Range	90dB ref. +24dBu
Crosstalk	
Crosstalk	>80dB @ 1KHz >60dB @ 10KHz
IM & THD	
IM & THD	= 0.05% +24dBu
Input	
Max. Source Level	
Max. Source Level	+24dBu
Impedance	
Impedance	> 10K Ω balanced
Connector Type	
Connector Type	Lockable 5-pin terminal block
Output	
Max. Source Level	
Max. Source Level	+24dBu
Impedance	
Impedance	150 Ω balanced
Connector Type	
Connector Type	Lockable 5-pin terminal block
Redundant Power Supply	
Redundant Power Supply	Standard
Storage Temperature	
Storage Temperature	-40 $^{\circ}$ to +150 $^{\circ}$ F
Operating Temperature	
Operating Temperature	30 $^{\circ}$ to 100 $^{\circ}$ F ambient
Humidity	
Humidity	10% to 90 % non-condensing
Warranty	
Warranty	7 years
Protocols	
Protocols	SVS host, simple Kramer, and select others
Redundant Control Processor	
Redundant Control Processor	Optional
Control Panels (Optional)	
Control Panels (Optional)	Supports SCP programmable control panels, XY & single bus control panels