

# **Adder AVX1016-US 16 Port High density fully featured USB/Video KVM Switcher**

## **Hardware compatibility**

Supports PC, RS/6000, Alpha, SGI, Sun and Apple with USB / PS/2 / Sun style keyboard and mouse and VGA video interfaces

## **Software compatibility**

Operates with all known software and operating systems including Windows (all), DOS, Linux, Unix, BSD, all Sun OS, all Mac OS, NetWare etc.

## **Computer connections at switch**

RJ45

## **Computer connections at computer**

Video: HDD15, Keyboard/Mouse: choice of USB, PS/2 and Sun MiniDin8 Audio (optional): 3.5mm stereo jack

## **Local KVM console connection**

Video: HDD15, Keyboard/Mouse: USB type A, Audio: 3.5mm stereo jack

## **Physical design**

1U high 198mm / 7.92"(w), 44mm / 1.76"(h), 120mm / 4.8"(d), 750g / 1.65 lbs. 1 per 1U or 2 per 1U rack mount kits available

## **Power connection**

2.5mm DC jack, power adapter included

## **Other connectors**

Remote KVM console: RJ45, Options (flash upgrade, sync with other CATx1000 and RS232 triggered power switches): DB9 female

## **Power**

100-240VAC 50/60Hz input to power adapter, 5VDC 2A output from power adapter

## **Operating temperature**

0 - 40 deg C (32 to 104 deg F)

## **Approvals**

CE, FCC

## **Order codes**

AVX1008-XX: 8 port version AVX1016-XX: 16 port version

XX= Mains Lead Country Code: UK = United Kingdom US = United States EURO = Europe AUS = Australia

## **Additional accessories**

RMK4S: Single rack brackets RMK4D: Dual rack brackets CAB-9M/9F-2M Serial option cable