

**Electro-Voice PA4150L120V PA Series Amplifier (2x 160W/4 Ohms/2RU)**

Weight Net	18kg (39.68 lbs)
Depth	406mm (15.98")
Width	483mm (19.02")
Height	88mm (3.46")
Amplifier Gain	30dB
Channels	4
Continuous Rated Power (1 kHz, THD 1%) 2Ω	160Watts
Continuous Rated Power (1 kHz, THD 1%) 4Ω	160Watts
Continuous Rated Power (1 kHz, THD 1%) 8Ω	100Watts
Continuous Rated Power (20-20 kHz, THD<0,2%) 4Ω	150Watts
Continuous Rated Power (20-20 kHz, THD<0,2%) 8Ω	75Watts
Crosstalk	< < -75dB (ref. 1kHz, @ 10% rated output power)
DIM 30	< 0.1%
Frequency Response (-3 dB)	< 10Hz - 40kHz (-1dB, ref. 1kHz)
Impedance	4/8Ω
Input Impedance (Balanced)	> 20kΩ
Input Sensitivity	0 dBu (775mV) (@ rated output power or voltage, 1kHz)
Intermodulation Distortion (SMPTE)	< 0.1%
Network Control (IRIS-Net)	No
Number of Channels	4
Rated output power (*rated load) THD < 0.2%, 20Hz - 20kHz	150/75W (4ω/8ω)
Rated output power (*rated load) THD < 1%, 1kHz	160/100W (4ω/8ω)
Signal-to-Noise Ratio (A-weighted)	101dB
Slew Rate	16V/μs
Total Harmonic Distortion	< 0.1%