

## PureLink HWCE Tx/Rx 4K HDMI/USB 2.0 HDBaseT Wall Plate Extender (Transmitter/Receiver) System up to 130ft

Technical Specifications	
<b>Connector Type/s (Tx/Wall Plate)</b>	<b>Inputs:</b> (1) HDMI Type A [19-pin female], (1) 3.5mm stereo audio, (1) USB Type B, (1) RS-232 [3-pin phoenix], (1) DC 24V/GND [2-pin phoenix] <b>Output:</b> (1) HDBaseT™ OUT [RJ45]
<b>Connector Type/s (Rx)</b>	<b>Input:</b> (1) HDBaseT™ IN [RJ45] <b>Outputs:</b> (1) HDMI Type A [19-pin female], (1) 3.5mm stereo audio, (1) USB Type A, (1) RS-232 [3-pin phoenix], (2) USB Type A
<b>Compliance</b>	HDMI 1.4, HDCP 2.2, USB 2.0
<b>Supported Bandwidth</b>	10.2 Gbps
<b>Supported Resolutions</b>	4K@50/60Hz (4:2:0), 4K@30Hz (4:4:4), 1080p@120Hz, 1080p 3D@60Hz
<b>Color Space</b>	RGB/YCbCr 4:4:4, YCbCr 4:2:2
<b>Color Depth</b>	8-bit, 10-bit, 12-bit
<b>HDMI Audio Formats</b>	LPCM, Dolby Digital/Plus/EX, Dolby True HD, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DSD
<b>Analog Audio Formats</b>	LPCM 2CH, LPCM 5.1, Dolby Digital 2/5.1CH, DTS 2/5.1CH
<b>Max Power Consumption</b>	9 Watts
<b>Power Supply</b>	Input: AC100 - 240V 50/60Hz Output: DC 24V/1A (US/EU standards, CE/FCC/UL certified)
<b>Dimensions (WxDxH)</b>	<b>TX:</b> 4.07"x1.81"x1.18" (103.5mm x 46mm x 30mm) <b>RX:</b> 5.51"x2.95"x0.91" (140mm x 75mm x 23mm)
<b>Weight</b>	<b>TX:</b> 0.36 lbs. (163g) <b>RX:</b> 0.44 lbs. (200g)