

RE97TX MICRO-HEADWORN CONDENSER MICROPHONE



- Lightweight, Durable
- Extremely flexible for precise positioning and long life
- Interchangable for Left or Right Ear
- Omnidirectional Polar Pattern Provides Clean Sound and Uniform Response
- Moisture Resistant
- For use with all Standard ElectroVoice and Telex Wireless Bodypack Transmitters.
- Also available un-terminated (RE97PT) and wired for Shure® TA4 bodypacks (RE97S)

The Electro-Voice® RE97Tx is an Ultra-low profile, omnidirectional, back-electret condensor headworn microphone ideal for applications such as Houses of Worship, Corporate AV, Theatre, and other venues where a full-range, natural, well balanced sound is required. The omnidirectional polar pattern provides a clean and accurate sonic quality and uniform output regardless of the microphone's position relative to the sound source. The RE97Tx is designed to be extremely flexible and easily formed to fit over the ear of any user. The malleable boom and earhook can be shaped to match virtually any contour. An elegant clothing clip to retain the cord and a removable windscreen complete the package.








www.electrovoice.com

Www.electrovoice.com
Americas
Telex Communications Inc.
12000 Portland Ave South,
Burnsville, MN 55337, USA
USA—Phone: 1-800-392-3497
Fax: 1800-955-6831
Canada—Phone: 1-866-505-5551
Fax: 1-866-336-8467
Latin America—Phone: 1-952-887-5532
Fax: 1-952-736-4212


Europe, Africa & Middle-East Germany: EVI Audio GmbH. Hirschberger Ring 45, D 94315, Straubing, Germany Phone: +49 9421 706-0 Fax: +49 9421 706-265 France: EVI Audio France S.A., Parc de Courcerin, Allée Lech Walesa, F 77185 Lognes, France Phone: +33 1-6480-0090 Fax: +33 1-6006-5103

UK: Shuttlesound, 4 The Willows Centre, Willow Lane, Mitcham, Surrey CR4 4NX, UK Phone: +44 208 646 7114 Fax: +44 208 245 5666

Polar Response:



Generating Element:	Condenser, back electret
Frequency Response:	50 – 15kHz
Polar Pattern:	Omnidirectional
Sensitivity, 1kHz (Open Circuit):	4.0mV / Pascal
Clipping Level:	>125 dB SPL
Equivalent Noise:	32 dBA
Dynamic Range:	93 dB
Output Impedance, 1kHz:	3000 ohms
Power Requirements:	5 VDC
Current Consumption:	310 uA
Polarity:	Positive pressure on diaphram produces a positive voltage on pin 2.
Dimensions	Boom length (as shipped): 3.4 in. (86.4 mm) Boom diameter: 0.080 in. (2.00 mm) Capsule diameter: 0.120 in. (3.05mm) Earhook diameter: 0.090 in. (2.30 mm)
Cable:	4 ft (1.22m) long, 0.077 in. (1.95mm) diameter
RE97Tx Connector Wiring:	Pin #1 – Ground, Shield Pin #2 – Audio Pin #3 – Bias Voltage Pin #4 – N/C
Accessories Furnished:	Windscreen Clothing Clip Gig Bag
Color:	Beige, Brown, Black
Net Weight:	0.6 oz. (17g) Mic only: 0.2 oz. (5.7g)



Asia & Pacific Rim Japan: EVI Audio Japan Ltd. 5-3-8 Funabashi, Setagaya-Ku, Tokyo, Japan 156-0055 Phone: +81 3-5316-5020, Fax: +81 3-5316-5031

China: Telex EVI Audio (Shanghai) Ltd. Room 2210-2215, Tower B, Far East International Plaza No. 317, Xianxia Road, Shanghai, China, PC: 200051 Phone: +86 (21) 6235-1677 Fax: +86 (21) 6235-1676 Hong Kong: Telex EVI Audio (HK) Ltd. Unit 5,1/F,Topsail Plaza 11 On Shum Street Shek Mun,Shatin HK Phone: +852 2351-3628 Fax: +852 2351-3329

Singapore: Telex Pte. Ltd. 3015A Ubi Road 1, 05-10 Kampong Ubi Industrial Estate, Singapore 408705 Phone: +65 6746-8760 Fax: +65 6746-1206