

ViewSonic VA2465SMH 23.6 inch LED SuperClear VA Technology Monitor/1920x1080/250 nits/HDMI/VGA Inputs

Display Size (in.):	24
Viewable Area (in.):	23.6
Panel Type:	MVA
Resolution:	1920 x 1080
Static Contrast Ratio:	3,000:1
Light Source:	LED
Brightness:	250 cd/m2
Colors:	16.7M
Response Time (Typical GTG):	7ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	40,000
Panel Surface:	3H Anti-glare, hard-coating
PC Resolution (max):	1920 x 1080
Mac® Resolution (max):	1920 x 1080
Internal Speakers:	1.5-watt (x2)
Eco Mode (Conserve):	13W
Eco Mode (optimized):	17W
Consumption (typical):	22W
Consumption (max):	30W
Voltage:	AC 100-240V (universal), 50-60Hz
Kensington Lock Slot:	1
Physical Controls:	1, 2, Down, Up, Power
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	20-90%
VESA Compatible:	100 x 100 mm
Frequency Horizontal:	24~82kHz
Frequency Vertical:	50~75Hz
Analog Sync:	Separate Sync, Composite Sync, Sync on Green
Tilt (Forward/Back):	5° / 20°
Net (lbs):	9.0
Net Without Stand (lbs):	7.8
Gross (lbs):	11.2
Net (kg):	4.1
Net Without Stand (kg):	3.6
Gross (kg):	5.3
Packaging (in.):	24.6 x 16.4 x 5.2
Physical (in.):	22.2 x 16.1 x 7.6
Physical Without Stand (in.):	22.2 x 13.7 x 1.8
Packaging (mm):	624 x 417 x 132
Physical (mm):	563.9 x 407.2 x 193.1
Physical Without Stand (mm):	563.9 x 347.1 x 46.0
3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1)	
Regulations:	cULus, FCC-B, ICES003, Energy Star 7.0, EPEAT Silver, UL-MX-CoC, Mexico Energy, CE, EMC, CB, RoHS, ErP, REACH, DoC, WEEE, TCO6.0, EAC, UkrSEPRO,

PACKAGE CONTENTS:	VA2465Smh monitor, Power cable, VGA cable, Quick Start Guide
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	Three-year limited warranty on parts, labor and backlight
UPC:	766907790825