



# LBN-10GTO/10GRO

Link Bridge HDMI 2.0 Video Encoder/Decoder **Over Optical 10G IP Network** 








#### **FEATURES**

- Supports HDMI 2.0 Video, together with Audio, RS-232. IR, LAN, and USB, over Optical 10G IP Network
- Visually Lossless Compression and Zero Latency
- HDMI 2.0 and HDCP 2.2 Compliant
- Supports pass-through 10/12-bit HDR sources (Point-to-Point and Genlock mode only)
- HDMI and DisplayPort Input at TX, and HDMI Output
- Provide Analog Audio Insertion and Extraction
- Bi-directional RS-232, IR, USB 2.0 Ports, as well as Local 10/100/1000Mbps LAN
- AV Processing supports video scaling, video wall, single-frame switching, multi-view window, and audio down-mixing















# LBN-10GTO/10GRO

## **VIDEO INPUT (TX)**

Video Formats	HDMI 2.0, DisplayPort 1.2
Connector	HDMI type A (HDMI 2.0)
	DisplayPort (DisplayPort 1.2)

## **VIDEO OUTPUT (RX)**

Video Formats	HDMI 2.0
Connector	HDMI type A

## **AUDIO (TX/RX)**

Audio Format	Analog L/R
Connector	3.5mm Jack

## **SERIAL DATA (TX/RX)**

Channel Capacity	1 bi-directional
Signal Format	RS-232
Data Rate	115,200 baud max
Connector	DB-9

## IR (TX/RX)

Channel Capacity	1 bi-directional
Data Rate	30-50KHz
Connector	3.5mm Jack

## ETHERNET (TX/RX)

Channel Capacity	1
Ethernet Speed	10/100/1000Base-T
Connector	RJ-45

#### **USB (TX/RX)**

Channel Capacity	1
Signal Format	USB 2.0
Connector	USB type B (TX), USB type A (RX)

#### **OPTICAL PORT (TX/RX)**

Transceiver type	10G SFP+ module
Number of fibers	2
Connector	LC

# STATUS LED INDICATORS (ENCODER/DECODER)

1	
Power	Indicates input power present
Link TX	Indicates 10G transmission activity
Link RX	Indicates 10G receive activity
Video	Indicates stable video
GbE	Indicates local Ethernet activity
USB	Indicates USB activity


#### **PHYSICAL**


Dimensions	8.47" (W) x 6.22" (D) x 1.85" (H)
Power	+12 VDC @ 3.0 Amps (Max.),
Operating Temperature	Up to 40-deg C, operating
Humidity	0 to 90%, non-condensing

#### **ORDERING INFORMATION**

LBN-10GTO	Encoder with HDMI/DisplayPort Input (300m multimode 10G SFP+ included)
LBN-10GRO	Decoder with HDMI Output (300m multimode 10G SEP+ included)

#### **PANEL DRAWINGS**













DOING MORE WITH ONE CABLE

2545 W. 237th St. Torrance, CA 90505 Phone:(800) 214-0222, Fax: (310) 530-5958 Email:Broadata@Broadatacom.com http://www.broadatacom.com