

Avenview DVI-PROWALL-12X 12-Display HDMI/DVI Video Wall Processor with Rotation

ITEM	DESCRIPTION
UNIT	DVI-PROWALL-12X
UNIT DESCRIPTION	12 Display Video Wall Processor (VideoWall Controller)
Video Bandwidth	DVI Single Link - 4.95Gbps
	HDMI[2.25G to 6.75Gbps]
	Component [30MHz],VGA
Supported Resolutions	Up to 1920x1200@60
Audio Support	No
Control	RS-232 / Ethernet
Embedded Video Mixer	Yes
Ability to Cascade	Yes (Upto 4 units 16 DVI Output Displays)
Input TMDS Signal	1.2 Volts (peak û peak)
ESD Protection	Human body model - 15kV (air gap discharge) & ±8kV (contact discharge)
Input	1x HDMI/DVI 1x HDMI/VGA/Component
Output	12x DVI-D/HDMI
DVI Connector Type	DVI-D [29-pin female, digital only]
RJ45 Connector	WE/SS 8P8C with 2 LED indicators
Enclosure	Metal case
Dimensions	438mm x 438mm x 89mm [17.25" x 17.25" x 3.5"]
Weight	30 lbs
Fixedness	Rack-mount with ears and Wall hanging holes
Power Supply	AC Power 100-240V
Power Consumption	60 W (max)
Operating Temperature	0~40°C [32~104°F]
Storage Temperature	-20~60°C [-4~140°F]
Relative Humidity	20~90% RH [no condensation]