

Kramer RC-63A(B) 6-Button Room Controller with Analog Volume Knob/Black

| | |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PORTS: | 1 RS-232 on terminal block connectors; 2 K-NET on terminal block connectors; 1 USB port. |
| OUTPUT: | 2 relays on terminal block connectors (36V AC or DC, 2A, 60V AC maximum on non-inductive load); 1 IR emitter on terminal block connectors. |
| POWER SOURCE: | 12V DC, 100mA. |
| FUSE: | 500mA, FSMD 2920. |
| ADAPTER: | SummitView™ kits: 12V, 5A; independent: 12V, 500mA. |
| DIMENSIONS: | 11.4cm x 2.9cm x 11.4cm (4.49" x 1.14" x 4.49") US; 15.2cm x 2.3cm x 8.6cm (5.98" x 0.9" x 3.39") and 15.2cm x 2.3cm x 8cm (5.98" x 0.9" x 3.15") EU W, D, H. |
| WEIGHT: | 0.14kg (0.31lbs) approx. |
| ACCESSORIES: | USB cable 0.91m (3ft), screwdriver, Windows®-based Kramer control software. |
| OPTIONS: | 12V DC, 0.5A Power supply; Kramer 3.5mm to IR Emitter Control Cable (C-A35/IRE-10); 15m (50ft) and 20m (65ft) IR emitter extension cables. |