

## Kramer 6410N Digital Audio to Balanced Stereo Audio Format Converter

<b>INPUTS:</b>	4 digital audio inputs: AES-3id on a terminal block connector; AES/EBU on a BNC connector; S/PDIF on an RCA connector; TOSLINK® optical connector.
<b>OUTPUTS:</b>	2 analog outputs: balanced line out on detachable terminal blocks; 3.5mm headphone jack.
<b>SAMPLE RATE CONVERSION:</b>	32kHz, 44.1kHz, 48kHz, 96kHz.
<b>CONVERSION GAIN:</b>	+12dB, +16dB, +20dB, +24dB.
<b>BANDWIDTH (+4dBu/-3dBu):</b>	20Hz to 22kHz.
<b>MAX. OUTPUT LEVEL:</b>	11.2Vpp @1kHz.
<b>S/N RATIO:</b>	88dB.
<b>AUDIO THD + NOISE:</b>	-92dB.
<b>AUDIO 2nd HARMONIC:</b>	0.003%.
<b>CONTROLS:</b>	Input selector buttons, 8 gain switches, headphones level rotary control knob, 2 LEDs: ON and LINK.
<b>POWER SOURCE:</b>	12V DC, 1.25A.
<b>DIMENSIONS:</b>	12cm x 6.95cm x 2.44cm (4.72" x 2.74" x 0.96") W, D, H.
<b>WEIGHT:</b>	0.3kg (0.66lbs) approx.
<b>ACCESSORIES:</b>	Power supply, mounting bracket.
<b>OPTIONS:</b>	RK-3T 19" rack adapter.