

Electro-Voice ZX1I100TW ZX1i Series 8 inch 2-Way Install Speaker with Transformer/70V/White/48Hz-20kHz

Frequency Response (-3 dB):	60 Hz-20 kHz
Frequency Range (-10 dB):	48 Hz-20 kHz
Rec. Hi-pass Frequency:	40 Hz
Axial Sensitivity:	92dB(1W/1m)
Max Calculated SPL:	121 dB
Coverage (HxV):	100x100
Rated System Power:	200 W Cont,400 W Prog., 800 W Peak
LF Transducer:	EV8L, 203 mm (8 in) Driver
HF Transducer:	DH2005,25 mm (1 in) Exit Compression Driver
Crossover Frequency:	1.7 kHz
Nominal Impedance:	8 Ohm
Minimum Impedance:	6 Ohm
"T" Version Wattage Taps:	70V-6,12.5,25,50,100,8 Ohm by p0V - 12.5, 25,50,100,8 Ohm bypass
Connectors:	4-Pin Phoenix Connector
Enclosure Material:	ABS resin
Suspension:	Integrated QuickSAM Heavy-Duty Strong-Arm Mounting Bracket
Grille:	Polyester Powder Coated, 18GA Galvanized Steel
Dimensions (HxWxD):	451 mm x 282 mm x 263 mm (18inx 11 inx 10in)
Net Weight:	8.4 kg (18.5 lb) without Transformer 10.4 kg (23.0 lb) with Transformer
Shipping Weight:	10.2 kg (22.5 lb) without Transformer 12.3 kg (27.0 lb) with Transformer