

Electro-Voice ZX1I90T ZX1i Series 8 inch 2-Way Install Speaker with Transformer/Black/70V/48Hz-20kHz

| | |
|-----------------------------|---|
| Frequency Response (-3 dB): | 60 Hz-20 kHz |
| Frequency Range (-10 dB): | 48 Hz-20 kHz |
| Rec. Hi-pass Frequency: | 40 Hz |
| Axial Sensitivity: | 94dB(1W/1m) |
| Max Calculated SPL: | 123 dB |
| Coverage (HxV): | 90x50 |
| Rated System Power: | 200 W Cont,400 W Prog., 800 W Peak |
| LF Transducer: | EV8L, 203 mm (8 in) Driver |
| HF Transducer: | DH2005,25 mm (1 in) Exit Compression Driver |
| Crossover Frequency: | 1.7 kHz |
| Nominal Impedance: | 8 Ohm |
| Minimum Impedance: | 6 Ohm |
| "T" Version Wattage Taps: | 70V-6.12.5,25,50,100,8 Ohm by p0V - 12.5,25,50,100,8 Ohm bypass |
| Connectors: | 4-Pin Phoenix Connector |
| Enclosure Material: | ABS resin |
| Suspension: | Integrated QuickSAM Heavy-Duty Strong-Arm Mounting Bracket |
| Grille: | Polyester Powder Coated, 18GA Galvanized Steel |
| Dimensions (HxWxD): | 451 mm x 282 mm x 263 mm (18 in x 11 in x 10 in) |
| Net Weight: | 8.4 kg (18.5 lb) without Transformer 10.4 kg (23.0 lb) with Transformer |
| Shipping Weight: | 10.2 kg (22.5 lb) without Transformer 12.3 kg (27.0 lb) with Transformer |