CHD3900-10

(6) 25 AWG Coax, (2) STP, Plenum

Description Multi-Conductor-Type Cable - (6) 26 AWG Coax with (2) 22 AWG Shielded Twisted Pairs -Plenum



Your Connection Company

Technical Specifications

Element 1

Coaxes:	25 AWG Bare Solid Copper
Dielectric:	Natural Foamed Fluorinated Ethylene Propylene, 0.074" Diameter
Outer Shield:	Aluminum (In) / Polyester Tape, 25% Overlap
Inner Shield:	38 AWG Tinned Copper, 95% Coverage
Jacket:	Polyvinyl Chloride, 0.010" Wall Thickness
Final Diameter:	0.106"
Number of Coaxes:	6
Color Code:	1. Red, 2. Green, 3. Blue, 4. Black, 5. White, 6. Yellow

Element 2

Twisted Pairs:	22 AWG (7/30) Tinned Copper, Stranded Individually Shielded Twisted Pairs
Shield:	Aluminum (In) / Polyester Tape, 25% Overlap
Drain Wire:	22 AWG (7/30) Tinned Copper
Jacket:	Polyvinyl Chloride .008" Wall Thickness
Final Diameter:	0.108"
Number of Pairs:	2
Color Code:	1. Red & Black 2. Black & White

Construction

Number of Coaxes:Elements 1 & 2Color Code:22 AWG (7/30) Tinned Copper, Over TapeOuter Jacket:Polyvinyl Chloride, 0.018" Wall ThicknessFinal Diameter:0.374"Color:Dark Blue

Approximate Weight:

115 lbs. per 1000 ft.

UL Listing

Type CL2P as Specified in Article 725 of the National Electric Code