

Covid CVD3900-13-500R (7) 26 AWG Coax/(2) 22-2 STP/Plenum Multi-Conductor Type Cable - 500ft Reel

Element 1	
Coaxes:	26 AWG (7/34), Tinned Copper,
Dielectric:	Stranded Natural Foamed Fluorinated Ethylene Propylene, 0.072" Diameter
Outer Shield:	Aluminum (In) / Polyester Tape, 25% Overlap
Inner Shield:	38 AWG Tinned Copper, 95% Coverage
Jacket:	Polyvinyl Chloride, 0.009" Wall Thickness
Final Diameter.:	0.102"
Number of Coaxes:	7
Color Code:	1. Red, 2. Green, 3. Blue, 4. Black, 5. White, 6. Yellow, 7. Orange
Element 2	
Twisted Pairs:	22 AWG (7/30) Tinned Copper, Stranded Individually Shielded Twisted Pairs
Shield:	Aluminum (In) / Polyester Tape, 25% Overlap
Drain Wire:	22 AWG (7/30) Tinned Copper
Jacket:	Polyvinyl Chloride .007" Wall Thickness
Final Diameter:	0.105"
Number of Pairs:	3
Color Code:	1. Red S. Black 2. Black & Yellow 3. White & Black
Construction	
Conductors:	Elements 1, 2
Jacket:	Polyvinyl Chloride
Final Diameter:	0.435"
Color:	Dark Blue