

**Electro-Voice SX300PIXW Sx Series 12 inch 2-Way 300W 70V Speaker (White/Weatherized)**

Frequency Range (-10 dB)	50 - 20000kHz
Weight Net	17.7kg (39.02 lbs)
Depth	312mm (12.28")
Width	429mm (16.89")
Height	586mm (23.07")
Color	White
Axial Sensitivity (SPL, 1 W @ 1 m)	99dB
Chassis Size	304.8mm (12")
Coverage (Nominal -6 dB) H	65° (Const.-dir. horn)
Coverage (Nominal -6 dB) V	65° (Const.-dir. horn)
Crossover Frequency	1500Hz
Directivity Index	11.1dB (+2.4/-4.1 dB)
Enclosure Material	Polypropylene Composite
Family	Sx
Flying	Yes
HF Transducer	1.25-inch DH3/2010A
Input Connections	2 four-pin Speakon
Internal Crossover	Yes
LF Transducer	12-inch DL12BFH
Max. SPL/1m (calc)	131/123dB (Low Z/100V)
Minimum Impedance	5Ω
Nominal Impedance (Passive)	8Ω
Power Rating	300W
Powered or Passive	Passive
Sensitivity 1 W/1 m	99dB
Speaker Type	Full-Range, Mid-High, Two-Way
System Power Handling (Continuous/Program/Peak)	300//1200Watts (Long-Term/Short-Term)
Transformer	Yes
Weatherized	Yes
Woofer Size	12inch