

## Electro-Voice EVIDC8.2HC 8 inch Waveguide Coupled Coaxial Speaker with Horn Loaded Ti Coated Tweeter

Frequency Range (-10 dB)	50 - 20000kHz
Weight Net	6kg (13.23 lbs)
Height	303mm (11.93")
Available Color	White (paintable surface)
Chassis Size	203.2 mm
Coverage (Nominal -6 dB)	75 (conical (@ &#38;#38;#62;1 kHz))
Diameter (Max)	320mm (12.6")
Enclosure Material	Steel enclosure and UL94V-0 rated baffle and bezel
Grille	Powder-coated steel
HF Transducer	1-inch (25 mm) Ti Mylar Laminate Dome
Input Formats	8 $\omega$ , 70 V, 100 V
LF Transducer	8-inch polypropylene cone plus waveguide
Mounting Systems	Integrated 3-point toggle anchors
Power Rating	300W
Regulatory Approvals	UL1480; EN54-24; UL2043
Sensitivity 1 W/1 m	93dB
Speaker Type	Ported cabinet, internally damped, two-way (passive crossover included)
System Power Handling (Continuous/Program/Peak)	100Watts (Overload Protected)
Transformer	Yes
Transformer Taps (Transformer Version Only)	(7.5 - 70 V only), 15, 30, 60
Weatherized	No