

Electro-Voice EVIDC8.2LP 8 inch Coaxial Speaker with Horn Loaded Ti Coated/Pair

Max Calculated SPL	60 watt Transformer coupled @ 4 meters: 92 dB 100 watt Direct coupled @ 4 meters: 95 dBdB
Connectors	Phoenix type removable, with scre terminals and "loop-thru", accepts 12 ga wire
Coverage (Conical)	110°
Cutout Size	10.75" (272mm)
Dimensions (H x Dia)	7.0" x 10.6 (178mm x 270mm)
Enclosure	Baffle- UL 94V-O rated AB Backcan-Zinc plated steel
Freq. Response (-10 dB)	50 Hz - 20 kHzdb
Grille	Perforated powder coated steel wit safety tether
HF Transducer	1 in (25 mm) Ti Mylar laminate
Impedance	8 Ohms nominal (transformer bypass)
LF Transducer	8 in. (200 mm) Polypropylene cone
Net Weight	11.0 lbs (5.0 kg)
Network	Network and transducers protected 12 dB/oct 2.6 kHz
Power Handling	75 W Cont. / 300 W Peak
Safety Agency Ratings	UL 1480 Safe for use in air handling spaces per UL 2043
Sensitivity (SPL 1W/1m)	91 dB
Shipping Weight:(pair)	24.0 lbs (11.0 kg)
Support Hardware	Tile bridge, backing plate support cutout template, paint shield
Transformer Taps	70V: 1.88, 3.75, 7.5, 15 or 30 100V: 3.75, 7.5, 15 or 30W Bypass: 8 Ohms