

## Electro-Voice EVID4.2TW EVID Series 70V 2-Way Speaker (White/Pair)

Frequency Response 1(-10 dB)	65Hz - 20kHz
Power Handling 2	200W Cont. Prog./400W Peak
Sensitivity 3	89 dB, 1W/1m
Impedance	8 ohms
Max SPL	113 db
Horizontal Coverage 4	120°
Vertical Coverage 4	80°
Crossover Frequency	2.2 kHz
LF Transducer	2 x 4" (100 mm)
HF Transducer	1" (25 mm)
Protection	Full System
Weather Resistance	Meets Mil Spec 810 humidity, salt spray, temperature and UV, and IEC 529 IP 34 splashproof ratings
Swing x Rotation	100° x 90°
Terminals	Phoenix Connector
Enclosure Material	ABS (paintable)
"t" Version Wattage Taps	70V: 3.75 W 70V/100V: 7.5W, 15W, 30W, 8 ohm bypass
Dim (H x W x D)	12.2" x 6.9" x 8.5" (234 mm x 127 mm x 165 mm)
Net Weight (each)	8.5 lbs (3.9 kg)
Shipping Weight (pair)	19 lbs (8.6 kg)
Included Accessories	SAM™, hex key

1. Half Space (wall mounting)
2. Continuous Program Rating: 3 dB greater than continuous pink noiserating (IEC-shaped pink noise with 6dB crest factor)
3. Avg: Half Space (wall mounting)
4. When mounted with long axis in vertical plane