

# IPGARD SDVN-1S-P Secure 1-port/single-head DVI KVM switch with dedicated CAC port and 4K support

<b>VIDEO</b>	
Format	DVI-D Single Link, DVI 1.0
Input Interface	(1) DVI-D 23-pin female
Output Interface	(1) DVI-I 23-pin female
Resolution	2560 x 1600 @ 60Hz; 3840x2160 @ 30Hz (w/HDMI-to-DVI adapter)
DDC	5 volts p-p (TTL)
Input Equalization	Automatic
Input Cable Length	Up to 20 ft.
Output Cable Length	Up to 20 ft.
<b>USB</b>	
Input Interface	(2) USB Type-B
Output	(2) USB 1.1 Type A for KM Devices
Emulation	Keyboard & Mouse
CAC	Configurable CAC
<b>AUDIO</b>	
Audio Input	(1) 3.5mm stereo audio
Audio Output	(1) 3.5mm stereo audio
<b>CONTROL</b>	
Front Panel	Front panel SELECT buttons
<b>OTHER</b>	
Power	External 100-240 VAC/12VDC2A @ 24W
Approvals	NIAPP PP 3.0, UL, CE, ROHS Compliant
Operating Temp.	+32 to +104°F (0 to +40°C)
Storage Temp.	-4 to 140°F (-20 to +60°C)
Humidity	Up to 80% (No Condensation)