

Hall Technologies SSW-HD-4 4-Input HDMI Seamless Switch with Real-Time Multiview Modes

- **Video Resolution:**
- **Output:** 1080p@60Hz, 1080i@60Hz, 720p@60Hz, 1024x768@60Hz, 1360x768@60Hz
- **Input:** 480i@60Hz, 480p@60Hz, 576i@50Hz, 576p@50Hz, 720p@50/60Hz, 1080i@50/60Hz, 1080p@24/30/50/60Hz, 800x600@60Hz, 1024x768@60, 1280x720@60Hz, 1920x1080@60Hz
- **Video Bandwidth:** Single-link to 165 MHz (4.95 Gbps)
- **Audio Standards:** PCM [2/5.1/7.1]CH, Dolby Digital 2~5.1CH, DTS 2~5.1CH, Dolby True HD and DTS-HD Master Audio
- **Input Ports:**
- 4 x HDMI Female with Locking Capability
- 1 x RS-232
- **Output Ports:**
- 1 x HDMI Female with Locking Capability
- 1 x S/PDIF audio out with RCA Connector
- **Power Supply:** 12 VDC @ 2.5A
- **ESD Protection:** Human Body model:
- 8kV (air-gap discharge)
- 4kV (contact discharge)
- **Dimensions:**
- Product: 9.85" (250mm) W x 4.65" (118mm) D x 1.25" (32mm) H
- Shipping: 11.50" (292mm) x 7.50" (190mm) x 3.00" (76mm)
- **Weight:**
- Product: 1.8 lbs (0.8 kg)
- Shipping: 2.95 lbs (1.3 kg)
- **Enclosure:** Metal
- **Operating Temperature:**
- Storage: -4 to +140 °F (-20 to + 60 °C)
- Operating: +32 to +122 °F (0 to +50 °C) 20% to 90% RH non-condensing