

## Electro-Voice EVF1121SBLK 12 inch 400W Front-Loaded Bass Element/Passive/Bi-Amp/Evcoat/Black

Frequency Range (-10 dB)	48 - 120kHz
Weight Net	26.2kg (57.76 lbs)
Depth	413.3mm (16.27")
Width	406mm (15.98")
Height	768.6mm (30.26")
Coverage (Nominal -6 dB)	Omnidirectional in normal operating range
Coverage (Nominal -6 dB) H	360°
Enclosure Material	13 Ply Weather Resistant Birch
Environmental Specs	Standard versions: IEC 60529 IP44. PI and FG versions: IEC 60529 IP55
Frequency Response (-3 dB)	70 - 98kHz
Grille	Standard versions: 16-ga Galvanneal, Powdercoat, with screen behind. PI and FG versions: 18-ga Stainless, Powdercoat, with hydrophobic cloth behind
Input Connections	Phoenix/Euroblock style screw terminals
Internal Passive Low-Pass Filter	100Hz (12 dB per octave)
LF Transducer	EVS12SB, 12 in (305mm) Driver
Max. SPL/1m (calc)	131dB
Minimum Impedance	Passive: 3.4, Biamp: 5.5Ω
Nominal Impedance (Passive)	Passive: 4, Biamp: 8Ω
Passive Power Handling	1600W peak
Recommended High-Pass Frequency	50Hz
Sensitivity 1 W/1 m	99dB
Speaker Type	Subwoofer
Suspension	(22) M10 Threaded Points (one EBK-M10-EVI kit of four forged eyebolts included)
System Power Handling (Continuous/Program/Peak)	400, 800, 1600Watts
Weatherized	No