

Electro-Voice EVF1121SFGW 12 inch 400W Front-Loaded Bass Element/Passive/Bi-Amp/Fiberglass/White

Freq. Response1 (-3 dB):	66 Hz - 100 Hz
Freq. Range1 (-10 dB):	48 Hz - 156 Hz
Rec. Hipass Frequency:	55 Hz
Axial Sensitivity1:	98 dB (1W/1m)
Max. Calculated SPL1 :	130 dB
Horizontal Coverage:	Omnidirectional
Vertical Coverage:	Omnidirectional
Power Handling:	400W Continuous, 1600W Peak
LF Transducer:	EVS12SB, 12 in (305mm) Driver
Nominal Impedance:	4 Ohms (Passive), 8 Ohms (Biamp)
Connectors:	(2) 4 Contact 10 AWG Phoenix/ EuroBlock Style Screw Terminal, Gland Nut with Input Panel Cover Included for Weatherizing
Enclosure Material:	13 Ply Weather Resistant Birch
Grille:	18 GA Stainless Steel with Hydrophobic Cloth and Rotatable Logo
Suspension:	(22) M10 Threaded Points
Dimensions (HxWx D):	30.26" x 16.00" x 16.27" (768.6mm x 406.3mm x 413.3mm)
Net Weight:	57.7 lb (26.2 kg)
Shipping Weight:	68.0 lb (30.8 kg)