

Electro-Voice EVF1122D/66WHT Premium 12 inch 2-Way Full-Range Loudspeaker/60x60deg/Evcoat/White

Frequency Range (-10 dB)	49 - 21000kHz
Weight Net	29.7kg (65.48 lbs)
Depth	413.3mm (16.27")
Width	406.3mm (16")
Height	768.6mm (30.26")
Coverage (Nominal -6 dB) H	60°
Coverage (Nominal -6 dB) V	60°
Crossover Frequency	1300Hz
Enclosure Material	13-ply weather-resistant birch with EVCoat
Environmental Specs	Standard versions: IEC 60529 IP44, PI and FG versions: IEC 60529 IP55
Frequency Response (-3 dB)	57 - 18000kHz
Grille	16 GA powder-coated galvalume with screen behind
HF Transducer	DH7N 3-inch (76mm) diaphragm compression driver
Input Connections	Phoenix/Euroblock style screw terminals; PI and FG versions include dual-gland-nut input-panel cover
LF Nominal Impedance	8Ω
LF Transducer	DVX3121A 12-inch (305mm) woofer
Max. SPL/1m (calc)	131dB
Minimum Impedance	6Ω
Nominal Impedance (Passive)	6Ω
Passive Power Handling	2400W peak
Recommended High-Pass Frequency	65Hz
Sensitivity 1 W/1 m	97dB
Shipping Weight	34.4kg (75.84 lbs)
Speaker Type	Full-Range, Two-Way
Suspension	(22) M10 threaded suspension points
System Power Handling (Continuous/Program/Peak)	600/1200/2400Watts
Weatherized	No