

Electro-Voice EVF1122D/96PIW Premium 12 inch 2-Way Full-Range Loudspeaker/90x60deg/Evcoat/PI-Weatherized/White

| | |
|---|--|
| Frequency Range (-10 dB) | 49 - 21000kHz |
| Weight Net | 29.7kg (65.48 lbs) |
| Depth | 413.3mm (16.27") |
| Width | 406.3mm (16") |
| Height | 768.6mm (30.26") |
| Coverage (Nominal -6 dB) H | 90° |
| Coverage (Nominal -6 dB) V | 60° |
| Crossover Frequency | 1300Hz |
| Enclosure Material | 13-ply weather-resistant birch with EVCoat |
| Environmental Specs | Standard versions: IEC 60529 IP44, PI and FG versions: IEC 60529 IP55 |
| Frequency Response (-3 dB) | 57 - 18000kHz |
| Grille | 16 GA powder-coated galvalume with screen behind |
| HF Transducer | DH7N 3-inch (76mm) diaphragm compression driver |
| Input Connections | Phoenix/Euroblock style screw terminals; PI and FG versions include dual-gland-nut input-panel cover |
| LF Nominal Impedance | 8Ω |
| LF Transducer | DVX312A 12-inch (305 mm) woofer |
| Max. SPL/1m (calc) | 131dB |
| Minimum Impedance | 6Ω |
| Nominal Impedance (Passive) | 8Ω |
| Passive Power Handling | 2400W peak |
| Recommended High-Pass Frequency | 65Hz |
| Sensitivity 1 W/1 m | 97dB |
| Shipping Weight | 34.4kg (75.84 lbs) |
| Speaker Type | Full-Range, Two-Way |
| Suspension | (22) M10 threaded suspension points |
| System Power Handling (Continuous/Program/Peak) | 600/1200/2400Watts |
| Weatherized | No |