

Electro-Voice EVF1152D/94FGB Single 15 inch 2-Way Full-Range Loudspeaker/90x40deg/Fiberglass/Weatherized/Black

Frequency Range (-10 dB)	58 Hz - 21 kHz
Weight Net	34.4kg (75.84 lbs)
Depth	466.6mm (18.37")
Width	469.8mm (18.5")
Height	768.6mm (30.26")
Coverage (Nominal -6 dB) H	90°
Coverage (Nominal -6 dB) V	40°
Crossover Frequency	1300Hz
Enclosure Material	13-ply weather-resistant birch with fiberglass finish
Frequency Response (-3 dB)	107 Hz - 18 kHz
Grille	18 GA stainless steel with hydrophobic cloth
HF Transducer	DH7N, 3" (76 mm) diaphragm compression driver
Input Connections	Dual four-pin 10 AWG Phoenix/Euro Block screw-terminals, CDG dual-gland-nut input panel cover included for weatherizing
LF Nominal Impedance	8Ω
LF Transducer	DVX3151A, 15" (381 mm) driver
Max. SPL/1m (calc)	134dB
Minimum Impedance	6.0Ω
Nominal Impedance (Passive)	8Ω
Passive Power Handling	2400W peak
Recommended High-Pass Frequency	55Hz
Sensitivity 1 W/1 m	100dB
Shipping Weight	39.1kg (86.2 lbs)
Speaker Type	Full-Range, Two-Way
Suspension	(22) M10 threaded suspension points
System Power Handling (Continuous/Program/Peak)	600/1200/2400Watts
Weatherized	Yes