

Kramer 576 HDMI Ultra-Reach Extender (Receiver) with RS-232/Loop over Any 2-Wire Cable

INPUTS

- 1 2-wire extra range HD signal on any one of the following connectors: RJ-45, 15-pin HD, or 2-pin terminal block

OUTPUTS

- 1 HDMI: On a female HDMI connector
- 1 S/PDIF: On an RCA connector
- 1 Balanced Stereo Audio: On a 5-pin terminal block connector

PORTS

- RS-232: On a 9-pin D-sub connector for serial link extension

VIDEO

- Max Resolution: 1080p60
- Compliance: HDCP 1.4

AUDIO

- Support: 2.0 channel PCM, 48kHz/44.1kHz sampling rate
- Bandwidth: 12kHz
- Analog THD + NOISE: 0.08% @ 1kHz at nominal level

EXTENSION LINE

- Full HD (1080p @60Hz): Up to 600m (2000ft)
- Baud Rate: 2400 to 115200, selectable

USER INTERFACE

- Indicator: ON LED
- Controls: Baud rate DIP-switches, Reset button

POWER

- Source: 5.2V DC, 4A
- Consumption: 5V DC, 1.5A

ENVIRONMENTAL CONDITIONS

- Operating Temperature: 0° to +40°C (32° to 104°F)
- Storage Temperature: -40° to +70°C (-40° to 158°F)
- Humidity: 10% to 90%, RHL non-condensing

STANDARDS COMPLIANCE

- Safety: CE, UL
- Environmental: RoHs, WEEE

ENCLOSURE

- Size: Mega Tool
- Type: Aluminum
- Cooling: Convection Ventilation

ACCESSORIES

- Included: 2 Power adapters, 2 power cords
- Optional: RK-T2B rack adapter

PRODUCT DIMENSION

- 18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00") W, D, H

PRODUCT WEIGHT

- 0.4kg (0.9lbs) approx.

SHIPPING DIMENSION

- 34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H

SHIPPING WEIGHT

- 1.0kg (2.1lbs) approx.