

Electro-Voice EVF1152S/99PIW 15 inch 2-Way Full-Range Loudspeaker/SMX Woofer/ND2B Driver/90x90deg/Evcoat/Pi-Weatherized/White

| | |
|---|--|
| Frequency Range (-10 dB) | 41 - 18000kHz |
| Weight Net | 32.1kg (70.77 lbs) |
| Depth | 466.6mm (18.37") |
| Width | 469.8mm (18.5") |
| Height | 768.6mm (30.26") |
| Coverage (Nominal -6 dB) H | 90° |
| Coverage (Nominal -6 dB) V | 90° |
| Crossover Frequency | 1450Hz |
| Enclosure Material | 13 Ply Weather Resistant Birch |
| Environmental Specs | Standard versions: IEC 60529 IP44 |
| Frequency Response (-3 dB) | 70 - 14000kHz |
| Grille | Standard versions: 16 GA Galvanneal, Powdercoat, with Rotatable Logo |
| HF Transducer | ND2B, 2 in (51 mm) Diaphragm Compression Driver |
| Input Connections | Phoenix/Euroblock style screw terminals |
| LF Transducer | SMX2151, 15 in (381mm) Driver |
| Max. SPL/1m (calc) | 134dB |
| Minimum Impedance | 6Ω |
| Nominal Impedance (Passive) | 8Ω |
| Passive Power Handling | 2000W peak |
| Recommended High-Pass Frequency | 45Hz |
| Sensitivity 1 W/1 m | 101dB |
| Speaker Type | Full-Range, Two-Way |
| Suspension | (22) M10 Threaded Points |
| System Power Handling (Continuous/Program/Peak) | 500/1000/2000Watts |
| Weatherized | No |