

Electro-Voice EVF2121SPIW Dual 12 inch Front-Loaded Subwoofer/Bi-Amp/Evcoat/Pi-Weatherized/White

Frequency Range (-10 dB)	41 - 330kHz
Weight Net	37.4kg (82.45 lbs)
Depth	467mm (18.39")
Width	470mm (18.5")
Height	768.6mm (30.26")
Coverage (Nominal -6 dB)	Omnidirectional in normal operating range
Coverage (Nominal -6 dB) H	360°
Enclosure Material	13-ply weather-resistant birch
Environmental Specs	Standard versions: IEC 60529 IP44. PI and FG versions: IEC 60529 IP55
Frequency Response (-3 dB)	54 - 145kHz
Grille	Standard versions: 16-ga Galvanneal, Powdercoat, with screen behind. PI and FG versions: 18-ga Stainless, Powdercoat, with hydrophobic cloth behind
Input Connections	Phoenix/Euroblock style screw terminals; PI and FG versions include dual-gland-nut input-panel cover
LF Transducer	Two EVS12SB 12-inch (305 mm) driver
Max. SPL/1m (calc)	135dB
Minimum Impedance	Passive: N/A, Biamp: 2.8Ω
Nominal Impedance	Passive: N/A, Biamp: 4Ω
Passive Power Handling	3200W peak
Recommended High-Pass Frequency	45Hz
Sensitivity 1 W/1 m	100dB
Speaker Type	Subwoofer
Suspension	(22) M10 Threaded Points (one EBK-M10-EVI kit of four forged eyebolts included)
System Power Handling (Continuous/Program/Peak)	800, 1600, 3200Watts
Weatherized	No