

# Kramer SM40NU-N HighSecLabs 4-Port KM Switch with USB 3.0 Port

## CONSOLE PORTS

- 2 USB-A connectors for keyboard and mouse
- 4 USB-A 3.0 connectors for USB devices
- 1 3.5mm mini jack for unbalanced stereo audio
- 1 3.5mm mini jack for microphone
- 1 RJ-45 connector for control (RDC)

## COMPUTER PORTS

- 4 USB-B connectors for keyboard and mouse
- 4 USB-B 3.0 connectors for USB devices
- 4 3.5mm mini jacks for unbalanced stereo audio
- 4 3.5mm mini jack for microphone

## POWER CONSUMPTION

- 12V DC, 1.5A

## AC INPUT

- 100V to 240V AC

## POWER TYPE

- External

## OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

## STORAGE TEMPERATURE

- -20° to +60°C (-4° to 140°F)

## HUMIDITY

- 0% to 80%, RH non-condensing

## SUPPORTED OS

- Windows, Linux, Mac

## PRODUCT CERTIFICATION

- CE, RCM, FCC class B, VCCI, TUV US, TUV Canada

## PRODUCT LIFE-CYCLE

- 10 years