

Electro-Voice 1829BT 60 Watt/70V Driver for CDP Projectors and Reentrant Horns/Weather Resistant

Frequency Response:	280 - 8.000 Hz
Power Handling, 8 Hours, 6-dB Crest Factor:	60 watts (500-5,000 Hz pink noise)
Impedance. Nominal:	16 ohms
Minimum:	11 ohms (FC100 horn)
Sound Pressure Level at 1 Meter, 1 Watt Input Averaged, Pink Noise Band-Limited from 300- 3,000 Hz:	105 dB on FC100 horn
Voice Coil Diameter:	5.08 cm (2.0 in.)
Magnet Weight:	0.45 kg (1.0 lb)
Magnet Material:	Strontium ferrite
Flux Density:	1.38 Tesla
Construction:	Rugged weatherproof finish fo outdoor use
Mechanical Construction of Driver:	1 3/8"-18 thread allows the 1829BT to be mounted on most University Sound horns
Recommended Horns:	FC100, Cobra flex I IB. Cobraflex III
Dimensions:	
Diameter:	13.5 cm (5.3 in.)
Length:	16.2 cm (6.4 in.)
Net Weight:	4.5 kg (9.8 lb)
Shipping Weight:	4.8 kg (10.6 lb)