

Electro-Voice EVU1062/95BLK Single 6.5 inch Two-Way 90x50deg Full-Range Loudspeaker System/Black

Frequency Range (-10 dB)	65 - 20000kHz (Half space)
Weight Net	6.53kg (14.4 lbs)
Depth	207mm (8.15")
Width	370mm (14.57")
Height	209mm (8.23")
Color	Black
Axial Sensitivity (SPL, 1 W @ 1 m)	92dB
Connector Type	4-pin Phoenix/Euroblock screw terminals (up to 10 AWG wire)
Coverage (Nominal -6 dB) H	90°
Coverage (Nominal -6 dB) V	50°
Enclosure Material	9-ply hardwood plywood
Finish	Textured paint
Frequency Response (-3 dB)	110 - 16000kHz (Half space)
Grille	18-gauge steel with cloth behind
HF Transducer	One 1.3-inch (33 mm) diaphragm ICT-1-8 compression driver
LF Transducer	One 6.5-inch (165 mm) ICT-6.5-8 woofer
Max. SPL/1m (calc)	120dB
Minimum Impedance	6Ω
Nominal Impedance	8Ω
Passive Power Handling	640W peak
Power Rating	640W
Recommended High-Pass Frequency	90Hz
Shipping Weight	9.12kg (20.11 lbs)
Speaker Type	Full-Range, Two-Way
Suspension	(6) M8 threaded points
System Power Handling (Continuous/Program/Peak)	160//640Watts (EIA RS-426A (eight hours))
Waveguide	6 in. x 6 in., rotatable
Weatherized	No