

## Electro-Voice EVU1082/95WHT Single 8 inch Two-Way 90x50deg Full-Range Loudspeaker System/White

Frequency Range (-10 dB)	65 - 20000kHz (Half Space)
Weight Net	7.4kg (16.31 lbs)
Depth	237mm (9.33")
Width	409mm (16.1")
Height	247mm (9.72")
Color	White
Axial Sensitivity (SPL, 1 W @ 1 m)	95dB
Connector Type	4-pin Phoenix/Euroblock screw terminals (up to 10 AWG wire)
Coverage (Nominal -6 dB) H	90°
Coverage (Nominal -6 dB) V	50°
Enclosure Material	9-ply hardwood plywood
Finish	Textured paint
Frequency Response (-3 dB)	110 - 16000kHz (Half Space)
Grille	18-gauge steel with cloth behind
HF Transducer	One 1.3-inch (33 mm) diaphragm ICT-1-8 compression driver
LF Transducer	One 8-inch (203 mm) ICT-8-8 woofer
Max. SPL/1m (calc)	123dB
Minimum Impedance	6Ω
Nominal Impedance	8Ω
Passive Power Handling	700W peak
Power Rating	700W
Recommended High-Pass Frequency	90Hz
Shipping Weight	10.3kg (22.71 lbs)
Speaker Type	Full-Range, Two-Way
Suspension	(6) M8 threaded points
System Power Handling (Continuous/Program/Peak)	175//700Watts (EIA RS-426A (eight hours))
Waveguide	6 in. x 6 in., rotatable
Weatherized	No