

## Electro-Voice EVU2062/95WHT Dual 6.5 inch Two-Way 90x50deg Full-Range Loudspeaker System/White

Frequency Range (-10 dB)	70 - 20000kHz (Half Space)
Weight Net	11.3kg (24.91 lbs)
Depth	207mm (8.15")
Width	533mm (20.98")
Height	209mm (8.23")
Color	White
Axial Sensitivity (SPL, 1 W @ 1 m)	94dB ((1W/1M))
Connector Type	4-pin Phoenix/Euroblock screw terminals (up to 10 AWG wire)
Coverage (Nominal -6 dB) H	90°
Coverage (Nominal -6 dB) V	50°
Enclosure Material	9-ply hardwood plywood
Finish	Textured paint
Frequency Response (-3 dB)	100 - 16000kHz (Half Space)
Grille	18-gauge steel with cloth behind
HF Transducer	One 1.3-inch (33 mm) diaphragm ICT-1-8 compression driver
LF Transducer	Two 6.5-inch (165 mm) ICT-6.5-8 woofers
Max. SPL/1m (calc)	125dB
Minimum Impedance	6Ω
Nominal Impedance	8Ω
Passive Power Handling	1400W peak
Power Rating	1200W
Recommended High-Pass Frequency	90Hz
Shipping Weight	14.2kg (31.31 lbs)
Speaker Type	Full-Range, Two-Way
Suspension	Six M8 threaded points
System Power Handling (Continuous/Program/Peak)	300//1200Watts (EIA RS-426A (eight hours))
Waveguide	6 in. x 6 in., rotatable
Weatherized	No