

Electro-Voice COBRAFLEXIIB Folded Sectoral Horn for 1824S/all 1828/all 1829/7110XC/all ID30 and all ID60 Drivers (Gray)

Horizontal Beamwidth:	80° @ 2 kHz (see Figure 2)		
Vertical Beamwidth:	60° @ 2 kHz (see Figure 2)		
Directivity Factor Rθ (Q):	9.1 @ 2 kHz (see Figure 3)		
Usable Low-Frequency Limit:	250 Hz		
Construction:	High impact acrylonitrile butadiene styrene (ABS) with ultraviolet light inhibiting grey paint finish. Positive-lock painted steel U-bracket.		
Mechanical Construction of Driver:	Threaded metal throat insert to accommodate a screw-in driver with a throat opening of 0.7 inch to 1.0 inch diameter and a standard 1 3/8"-18 thread.		
Dimensions:			
Height:	23.5 cm (9.3 in.)		
Width:	47.0 cm (18.5 in.)		
Depth:	26.0 cm (10.3 in.)		
Net Weight:	2.3 kg (5.1 lb)		
Shipping Weight:	3.0 kg (6.7 lb)		
Recommended Horns:			
ID30C-8	7110XC	ID30C-16	1824S
ID30CT	1828R	ID60C-8	1828T
ID60C-16	1829	ID60T	ID75