

Electro-Voice MM2TC 25-Watt Paging Surface/Bulkhead Mount Projector (16 Ohms/Gray)

Frequency Response:	800-5,000 Hz \pm 5 dB (see Figure 3)
Power Handling, 8 Hours, 6 dB Crest Factor:	25 watts (500-5,000 Hz pink noise)
Impedance	16 ohms
Sound Pressure Level at 1 Meter, 1 Watt Input Average, Pink Noise Band-Limited from 800-5,000 Hz:	104 dB
Horizontal Beamwidth:	82 0 @ 2 kHz (see Figure 2)
Vertical Beamwidth:	82 0 @ 2 kHz (see Figure 2)
Directivity Factor R θ (Q):	10.25 @ 2 kHz
Usable Low-Frequency Limit:	600 Hz
Construction:	Rugged die-cast aluminum case and transformer housing. Diaphragm is phenolic impregnated linen-base. All metal speaker parts are of anodized aluminum with baked-on acrylic paint. A cable entrance is provided on the bottom side
Voice-Coil Diameter:	5.1 cm (2.0 in.)
Magnet Weight:	0.93 kg (2.1 lb) with plates
Magnet Material:	Alnico V
Dimensions	
Height:	25.4 cm (10.0 in.)
Width:	16.4 cm (6.4 in.)
Depth:	11.3 cm (4.4 in.)
Net Weight:	4.0 kg (8.8 lb)
Shipping Weight:	4.5 kg (10.0 lb)