

Electro-Voice PA60/EV 60-Watt/8 Ohm 80x50deg Paging Projector

Frequency Response:	600-6,500 Hz \pm 5 dB (see Figure 3)
Power Handling, 8 Hours, 6 dB Crest Factor:	60 watts (500-5,000 Hz pink noise)
Impedance	Nominal: 8 ohms
Sound Pressure Level at 1 Meter 1 Watt Input Averaged, Pink Noise Band-Limited from 800 to 5,000 Hz:	107 dB
Horizontal Beamwidth:	80° @ 2 kHz (see Figure 2)
Vertical Beamwidth:	50° @ 2 kHz (see Figure 2)
Directivity Factor R θ (Q):	7.9 @ 2 kHz
Usable Low-Frequency Limit:	400 Hz
Construction:	High-impact acrylonitrile butadiene styrene (ABS) with ultraviolet light inhibiting mesa tan finish. Positive-lock painted steel swivel bracket. PA60M is white in color and has stainless steel hardware for marine use.
Voice-Coil Diameter:	3.81 cm (1.5 in.)
Magnet Weight:	0.28 kg (0.63 lb)
Magnet Material:	Strontium ferrite
Flux Density:	1.25 Tesla
Dimensions	
Height:	28.0 cm (11.0 in.)
Width:	16.5 cm (6.5 in.)
Depth:	21.6 cm (8.5 in.)
Net Weight:	1.8 kg (4.1 lb)
Shipping Weight:	2.1 kg (4.6 lb)