

PureLink VIP-CAM-100 H.264 IP Camera with 3G-SDI Output

Technical Specifications	
Image Sensor	1/2.8" Exmor CMOS, 2.14MP
HD-SDI Signal Formats	1080p/60, 1080p/30, 1080i/60, 720p/60, 720p/30 1080p/50, 1080p/25, 1080i/50, 720p/50, 720p/25
Focal	f = 4.7mm - 94.0mm
Iris	F1.6 - F3.5
Optical Zoon	20X
Digital Zoon	12X
Shortest Focus Distance	10mm - 1.000mm
Field of View	59.5° - 2.9°
Minimum Illumination	0.5Lux (Color), 0.1Lux (B/W)
Shutter Speed	1/1 ~ 1/10,000s
AGC	Auto/Manual
White Balance	Auto, Indoor, Outdoor, One Push, Manual, Auto Track
AE Control	Auto, Manual, Shutter Priority, Iris Priority
S/N Ratio	≥ 50db
Pan & Tilt	
Pan Range	-170° ~ +170°
Tilt Range	-30° ~ +90°
Pan Speed	0.1° ~ 120°/s
Tilt Speed	0.1° ~ 90°/s
Preset Number	256
OSD	Available
Image Flip	Enabled
Network	
Maximum Image Size	1920x1080 @60fps
Video Compression	H.265, H.264
Audio Compression	AAC
Protocol	HTTP/RTP/TCP/UDP/RTSP/RTMP/ONV1F
Network Support	Dual Stream; up to (10) simultaneous users
Interface	
Ethernet	RJ45, 100M
Video Output	HD-SDI
Control Interface	RS-232, IR, RS-485
General	
Control Protocol	VISCA and Daisy Chain Support, PELCO-P, PELCO-D
Address	0~63
Power Supply	DC 12V
Power Consumption	15W
Operating Temperature	0° C ~ 40° C
Storage Temperature	-20° C ~ 60° C
Dimensions	8.9" x 6.2" x 8.1"
Weight	1.7 kg
Enclosure	Gray