

## **Gefen EXT-UHDA-HBTL-RX 4K UHD HDMI/HDBaseT Extender (Receiver) with Audio De-Embedder/POH up to 40m/130ft**

- Maximum TMDS Clock: 300 MHz
- Total Signal Bandwidth/Data Rate: 10.2 Gbps
- Video Output Connector: (1) HDMI Type A 19-pin, female
- Link Connector: (1) RJ-45, shielded
- L/R Analog Audio Output port: (1) 3.5mm mini-stereo jack
- Optical Digital Audio Output port: (1) TOSLINK®
- Coaxial Digital Audio Output port: (1) RCA, female
- RS-232 port: (1) 3-pin Phoenix
- IR In/Ext port: (1) 3.5mm mini-stereo jack
- IR Out port: (1) 3.5mm mini-mono jack
- IR Extender type: EXT-RMT-EXTIRN
- Power Indicator LED: (1) Blue
- Link Indicator LED: (1) Green
- HDCP Indicator LED: (1) Green
- RS-232 Pass-Thru/Prog Switch: (1) 3-position, slide-type
- Power Supply: (1) 12V DC, locking, 5.5mm barrel/2.1mm pin
- Power Consumption 9W maximum: Not powering a Sender
- 22W maximum: Powering a Sender
- Operating Temperature: +32 to +122 °F (0 to +50 °C)
- Operating Humidity: 5% to 90% RH, non-condensing
- Storage Temperature: -4 to +185 °F (-20 to +85 °C)
- Storage Humidity: 0% to 95% RH, non-condensing
- MTBF: 50000 hours
- Overall Dimensions (W x H x D, not including the connectors): Not including the mounting brackets: 6" x 0.65" x 4" (152mm x 17 x 100mm), Including the mounting brackets: 7" x 0.65" x 4" (178mm x 17 x 100mm)
- Net Weight: 0.6 lbs. (0.27 kg)
- Shipping Weight: 1.5 lbs (0.7 kg)

\* Features and specifications are subject to change without notice.