

Gefen EXT-UHDV-HBTL5-TX 4K UHD Multi-Format 2x1 HDMI/VGA/HDBaseT Extender (Transmitter) with Scaler/Auto-Switching/POH

- Recommended Receiver: EXT-UHDA-HBTL-RX
- Maximum TMD5 Clock: HDMI Input: 600 MHz / Extension System: 300 MHz
- Total Signal Bandwidth/Data Rate: HDMI Input: 18 Gbps / Extension System: 10.2 Gbps
- Video Input Connector: (1) HDMI Type A 19-pin, female / (1)VGA HD-15, female
- L/R Analog Audio Input port: (1) 3.5mm mini-stereo jack
- Link Connector: (1) RJ-45, shielded
- RS-232 port: (1) 3-pin Phoenix
- IR In/Ext port: (1) 3.5mm mini-stereo jack
- IR Out port: (1) 3.5mm mini-mono jack
- IR Extender type: EXT-RMT-EXTIRN
- Firmware Update port: (1) USB-Mini-B, female
- Power Indicator LED: (1) Blue
- HDMI Input Indicator LED: (1) Green
- VGA Input Indicator LED: (1) Green
- Auto-Switch-On Indicator LED: (1) Green
- Input Select Switch (hold to select Auto or Manual): (1) tact-type
- Menu (On Screen Display) Select Switch: (1) tact-type
- Volume Up and Down Switches (hold both for Mute): (2) tact-type
- Power Supply Connector: (1) 5.5mm barrel/2.1mm pin, Locking
- Power Supply: (1) 12V DC, locking, 5.5mm barrel/2.1mm pin
- Power Consumption: Not powering a Receiver: 9W maximum / Powering a Receiver: 22W maximum
- Operating Temperature: +32 to +122 °F (0 to +50 °C)
- Operating Humidity: 5% to 90% RH, non-condensing
- Storage Temperature: -4 to +185 °F (-20 to +85 °C)
- Storage Humidity: 0% to 95% RH, non-condensing
- MTBF: 50000 hours
- Dimensions (W x H x D, not including the connectors): Not including the mounting brackets: 7.7" x 0.93" x 4" (195mm x 24 x 100mm) / Including the mounting brackets: 8.7" x 0.93" x 4" (221mm x 24 x 100mm)
- Net Weight: 0.8 lbs (0.35 kg)
- Shipping Weight: 1.9 lbs (0.9 kg)